

CAMBO

WHERE TRADITION MEETS VISION

CAMBO FOTOGRAFISCHE INDUSTRIE BV
HAATLANDERDIJK 45/P.O.BOX 200
NL-8260 AE KAMPEN
THE NETHERLANDS
PHONE: +31 38 3314644
FAX: +31 38 3315110
EMAIL: info@cambo.com
WEB: www.cambo.com



X2-PRO

X2-PRO

A New Twist On an Old Photographic Standard



Top View



Front View



Side View

CAMBO X2-PRO VIEW CAMERA SYSTEM

Perfect for product and architectural photographers alike, Cambo's innovative X2-PRO provides perspective- and image-control movements for your digital SLR camera. Simply mount your camera body and a lens to the X2-PRO and you'll immediately benefit from its ultra-fine, front-standard lateral and vertical shifts, swings and tilts.

Cambo's patented CROSSGEARING drives offer precision, liquid-smooth fine-focusing and lens-plane movements that will allow you to control perspective and image placement on anything from interiors and exteriors of buildings to table-top product shots in the studio.

The X2-PRO system is compatible with today's finest digital SLR cameras such as Canon's 1Ds series, 5D, 20D, 30D; 40D; Nikon's D3 and D300 bodies; Fujifilm's S5 body and Mamiya's ZD body. Cambo's dedicated camera-mounting

system places each model digital SLR in the exact optical center of the camera's sensor for on-axis movements and features a quick-release for switching from landscape to portrait format without removing the bellows.

Accepting a wide range of lenses from 28 to 150mm, the Cambo X2-PRO lets the photographer choose from their existing Schneider, Rodenstock, Hasselblad and Mamiya lenses, or take advantage of the latest digital lenses from Schneider or Rodenstock. There is also a choice of flat and recessed lensboards, depending upon which lens focal length you are using.

While the era of digital imaging has changed the way many people think about photography, there is still a demand for high-quality product and architectural photography with perspective corrections, and the X2-PRO is the newest solution.

X2-PRO SPECIFICATIONS

Weight of body only: 1.9kg (4.2 lbs.)
Weight including bellows and camera-mounting block: 2.1kg (4.6 lbs.)

Size: 26.3 x 29.3 x 19.5cm
(10.4 x 11.5 x 7.7") (h x w x d)

FRONT-STANDARD GEARED MOVEMENTS

Horizontal Shift: 17.5mm Left/17.5mm Right

Vertical Shift: 17.5mm Up/17.5mm Down

Tilt Angle: 20° Up/20° Down

Swing Angle: 20° Left/20° Right

Note: The amount of lens-panel movement is dependent upon size of the image-circle of the lens, as well as the chip size and the body/bayonet construction of the digital SLR camera.

Focusing Range

63 to 150mm (focal-length range without recessed lensplate)

X2-PRO Lens Compatibility

Schneider Apo-Digitar
28, 72, 80, 90, 100, 120 and 150mm

Rodenstock Apo-Sironar Digital
90, 105, 135 and 150mm

Hasselblad CF lenses (with adapter)

Mamiya 645 Pro lenses (with adapter)*
* Only in combination with Canon bodies

Mamiya RB/RZ lenses (with adapter)

Digital SLR Compatibility

Canon 1D(s) series and 5D/20D/30D/40D
Nikon D3, D2x, D300, D200

Fujifilm S5, S3 and Mamiya ZD.

Other mounts will follow as new digital-SLR bodies are introduced. Check with www.cambo.com

All models and technical specifications are subject to change without notice.



Dedicated camera-mounting bracket.